

Our Flex Pro Panels are the "Finest" Heating Systems in the World !!

Features & Benefits

- Time Saving Installation
- Powder Coated Steel Panel
- Modulating Electric Boiler
- High Quality Grundfos Pump
- Water Delivery Set Point Knob
- Fill System Gate & Ball Valve
- Slotted Holes for Easy Mounting
- High Quality Air Eliminator
- 30 # Relief Valve
- Closed Loop Exp Tank
- Modulating Status Led
- Press & Temp Gauges

Have Your System Up & Ready to Go In Minutes



Flex Pro Panel - Fig B

ISO 9001
CERTIFIED



Flex Pro Panel - Fig C



Flex Pro Panel - Fig A

Approved For Radiant Floor Heating Applications Per U.L. 499 Listing

HYDRO-SHARK II FLEX-PRO PANELS										
Model	Kw	Volts	Amps	Brkr	Btu	Lgth	Hgt	Depth	Lbs	Fig
FPP-07	7.2	240	30	(1) 40	24,573	26.25	32.75	10.00	54	A
FPP-10	9.6	240	40	(1) 50	32,765	26.25	32.75	10.00	54	A
FPP-12	12.0	240	50	(1) 70	40,956	34.50	32.75	10.00	64	B
FPP-14	14.4	240	60	(2) 40	49,147	34.50	32.75	10.00	69	B
FPP-19	19.2	240	80	(2) 50	65,529	34.50	32.75	10.00	69	B
FPP-22	21.6	240	90	(3) 40	73,721	41.50	32.75	12.50	82	C
FPP-24	24.0	240	100	(2) 70	81,912	34.50	32.75	12.50	69	B
FPP-29	28.8	240	120	(3) 50	98,977	41.50	32.75	12.50	82	C
FPP-36	36.0	240	150	(3) 70	122,868	41.50	32.75	12.50	82	C



HYDRO-SHARK II BOILERS ONLY										
Model	Kw	Volts	Amps	Brkr	Btu	Lgth	Hgt	Depth	Lbs	Fig
SH2-07	7.2	240	30	(1) 40	24,573	7.88	14.25	4.12	6	A
SH2-10	9.6	240	40	(1) 50	32,765	7.88	14.25	4.12	6	A
SH2-12	12.0	240	50	(1) 70	40,956	14.50	14.50	4.62	15	B
SH2-14	14.4	240	60	(2) 40	49,147	14.50	14.50	4.62	15	B
SH2-19	19.2	240	80	(2) 50	65,529	14.50	14.50	4.62	15	B
SH2-22	21.6	240	90	(3) 40	73,721	21.75	14.50	4.62	21	C
SH2-24	24.0	240	100	(2) 70	81,912	14.50	14.50	4.62	15	B
SH2-29	28.8	240	120	(3) 50	98,977	21.75	14.50	4.62	24	C
SH2-36	36.0	240	150	(3) 70	122,868	21.75	14.50	4.62	24	C



We carry a complete line of hydronic system components.



Phone 763-441-8303

Sales@EnergyProducts.biz

Fax 763-241-9628

STIEBEL ELTRON